

HYVLAR Modeller



Logosol PH360



Logosol PH365



Logosol PH260



Logosol PH260 ECO



Logosol DH410



Logosol SH410

	Logosol PH360	Logosol PH365	Logosol PH260	Logosol PH260 ECO	Logosol DH410	Logosol SH410	
Vikt	600 kg	925 kg	350 kg	350 kg	225 kg	195 kg	
Elsystem	16,25 kW	19,25 kW	13,2 kW	12,2 kW	6,2 kW	3,2 kW	
Elanslutning	3-fas, 400 V, 32 A	3-fas, 400 V, 32 A	3-fas, 400 V, 16 A	3-fas, 400 V, 16 A	3-fas, 400 V, 16 A	3-fas, 400 V, 16 A	
Matning	Standard: 3-15 m/min	Standard: 3-15 m/min	Standard: 2-12 m/min	Standard: 5m/min	Standard: 5 m/min	Standard: 5 m/min	
Hyvlar ned till	8 mm	8 mm	8 mm	8 mm	8 mm	6 mm (utan anhall)	
Max materialbredd	360 mm	360 mm	260 mm	260 mm	410 mm	410 mm	
Kapacitet	4-sidig hyvling bredd/höjd	360/10 till 130 mm	360/10 till 130 mm	15 till 260/10 till 100 mm	15 till 260/10 till 100 mm	–	
	2-sidig hyvling bredd/höjd	410/10 till 230 mm	410/10 till 230 mm	300/10 till 230 mm	300/10 till 230 mm	325/100 mm	
	Planhyvling bredd/höjd	510/10 till 230 mm	510/10 till 230 mm	410/10 till 230 mm	410/10 till 230 mm	410/10 till 250 mm	
	Klyvning höjd/diameter, klinga	–	–	–	–	–	80/180
Överkutter	Diameter	88 mm	88 mm	72 mm	72 mm	72 mm	
	Bredd	510 mm	510 mm	410 mm	410 mm	410 mm	
	Motoreffekt	5,5 kW	5,5 kW	4 kW	3 kW	3 kW/ 4 kW	3 kW/ 4 kW
	Avverkning planhyvling	0-8 mm	0-8 mm	0-8 mm	0-8 mm	0-8 mm	0-8 mm
	Profilutstick max	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm
Underkutter	Diameter	72 mm	72 mm	72 mm	72 mm	–	
	Bredd	410 mm	410 mm	300 mm	300 mm	–	
	Motoreffekt	4 kW	4 kW	3 kW	3 kW	–	
	Avverkning planhyvling	0-8 mm	0-8 mm	0-4 mm	0-4 mm	–	
Avverkning profilhyvling	Max. 10 mm	Max. 10 mm	Max. 10 mm	Max. 10 mm	–		
5:e kutter Sidokutter	Spindelaxelns diameter	30 mm	30 mm	30 mm	30 mm	30 mm	
	Kutterhöjd max	130 mm	130 mm	100 mm	100 mm	100 mm	
	Diameter max	140 mm	140 mm	140 mm	140 mm	140 mm	
	Motoreffekt	3 kW	3 kW	3 kW	3 kW	3 kW	–
	Spindel standard	–	30 mm	–	–	–	–
	Spindel för skaftfräsar	–	1-20 mm	–	–	–	–
Motoreffekt	–	3 kW	–	–	–	–	